



STRONGER POWER:

Low speed and strong torque wide scope and rapid acceleration response.

RELIABLE QUALITY:

Top component manufacturing all over the world unique integration design, reducing quantity of components by about 25%.



PRACTICALITY AND ECONOMY:

Exclusively sharing cummins software technology and fuel economy technologies which are top notch all over the world, saving over 8% on fuel consumption as compared to other engines.



CRASH & COMPLIANCE TEST:

DFAC is the first enterprise to pass ECE R29 frontal crash test and capping test in the light truck industry in Compliance with ECE R20-03 collision regulations.



RELIABILITY & PERFORMANCE TESTS:

800,000 Kilometres of high - temperatures, high-altitude and extremely cold weather endurance tests, as well as overall vehicle reliability tests.

13,650 component - tests, 461 system - level tests and over 6,000 vehicle level performance tests.



 **DONGFENG**

ASSET FINANCING

Limited stock available



Bank Financing



Monthly Instalments



Days Repayment Holiday

“Receiving your new truck is just the beginning of your relationship with us. Comprehensive aftersales solutions covering, genuine parts, driver training and certification, Additionally offered - mobile workshop services across the country.”

In the unlikely event that you should need our help, roadside assistance, available all year round. ”



Dfackeny@gmail.com
www.youtube.com/@DFACKENYA
<https://www.tiktok.com/@dfackeny>
www.dfackeny.com
<https://www.instagram.com/dfackeny>
<https://web.facebook.com/dfackeny>

Contact us:

Telephone: +254 0743065845
Email: dfackeny@gmail.com
Website: www.dfac.co.ke

DFAC KENYA LIMITED

Visit Our Showroom:
Mombasa Road - Plaza 2000
Opposite Sameer Business Park

 **DONGFENG**



COMPACT & MIGHTY

THE ULTIMATE SOLUTION FOR URBAN LOGISTICS

Longer Durability
Lower Fuel Consumption

Maximum Rugged Reliability
Unmatched Versatility

Comfort & Safety
Full Air Brake

EM97-101-201J

4T
KES. 3.3M
MODEL - EM97-101-201J

WEIGHT(KG)	GVW	6500
	Curb weight	2680
ENGINE	Engine Model	ISUZU JE493ZLQ3A
	Max. power	75kw/102HP@3600rpm
	Max. torque	285N·m@2100rpm
	Displacement	2771cc
	Emission Standards	Euro II
PERFORMANCE	Max. speed	110km/h
	Grade Ability	30%
DIMENSIONS(MM)	Wheel Base	3308
	Carriage inline dimension	4200*2100*2100
	Vehicle size	5978*2140*2275
DRIVE LINE	Clutch	Dry-Single plate, Hydraulic actuated control with servo assistance
	Gearbox	5 Forward & 1 Reverse (WLY5G32)
CHASSIS	Front axle	2.2T BANGLE
	Rear axle	3.5T BANGLE
	Final drive ratio	5.375
	Front suspension	6 Leaf spring with shock absorber
	Rear suspension	6+5 leaf spring
BRAKES	Service brakes	Vaccum assisted, Hydraulic dual circuit parking spring brake acting on rear axles, exhaust brake
	Parking brake	
OTHERS	Fuel tank capacity	100L Steel fuel tank
	Battery	12V/80Ah
	Tyre size	7.00R16 12PR

C72-944J

7T
KES.4.0M
MODEL - C72-944J

WEIGHT(KG)	GVW	11000
	Curb weight	3515
ENGINE	Engine Model	Cummins B125 33
	Max. power	92kw/125HP@2500rpm
	Max. torque	410N·m@1500rpm
	Displacement	3922cc
	Emission Standards	Euro II
PERFORMANCE	Max. speed	110km/h
	Grade Ability	30%
DIMENSIONS(MM)	Wheel Base	3800
	Carriage inline dimension	4800*2200*2200
	Vehicle size	6995*2230*2350
DRIVE LINE	Clutch	Dry-Single plate, Hydraulic actuated control with servo assistance
	Gearbox	6 Forward & 1 Reverse (FAST GEAR)
CHASSIS	Front axle	2.2T DANA
	Rear axle	5.5T DANA
	Final drive ratio	4.3
	Front suspension	8 Leaf spring / shock absorber
	Rear suspension	10+7 leaf spring
BRAKES	Service brakes	Full air - split pneumatic circuit parking spring brake acting on rear axles, exhaust brake
	Parking brake	
OTHERS	Fuel tank capacity	125L Steel fuel tank
	Battery	24V(12V*2/160Ah)
	Tyre size	215/75R17.5 16PR

CM90-101-902

10T
KES.4.1M
MODEL - CM90-101-902

WEIGHT(KG)	GVW	13000
	Curb weight	3696
ENGINE	Engine Model	Cummins EQB140-20
	Max. power	103KW/140HP@2500rpm
	Max. torque	502N·m@1500rpm
	Displacement	3922cc
	Emission Standards	EuroII
PERFORMANCE	Max. speed	80km/h
	Grade Ability	33%
DIMENSIONS(MM)	Wheel Base	4400
	Carriage inline dimension	6200*2200*2200
	Vehicle size	7995*2330*2550
DRIVE LINE	Clutch	Dry-Single plate, Hydraulic actuated control with servo assistance
	Gearbox	6 Forward & 1 Reverse (FAST GEAR)
CHASSIS	Front axle	3.9T DANA
	Rear axle	6.8T DANA
	Final drive ratio	4.875
	Front suspension	8 leaf spring with shock absorber
	Rear suspension	10+7 leaf spring
BRAKES	Service brakes	Full air-split pneumatic circuit parking spring brake acting on rear axles, exhaust brake
	Parking brake	
OTHERS	Fuel tank capacity	205L Steel fuel tank
	Battery	24V(12V*2/160Ah)
	Tyre size	8.5R20

The manufacturer reserves the right of technical alteration/change for better improvement without prior notice

We are Partners with TRUCKERS ASSOCIATION OF KENYA

